

Meeting House, the versatile modular system that gives you the freedom to configure and design workspaces, ideal for enhancing privacy, concentration and meetings in open office environments.




⟨⊘⟩

OPTIONAL FEATURES

PLANTER


▶ 25-mm thick melamine with shelf adjustable to 3 positions.



METAL PLANTER

Fitted inside the melamine planter.

1-mm thick sheet metal.




TECHNICAL SHEET

OPTIONAL FEATURES

TV/MONITOR MOUNT

- ▶ 1.2-mm thick folded sheet steel.
- ▶ Mount for screen up to 50"/35kg max. VESA 75mm to 200mm.



0.8-mm thick folded sheet steel cable riser

CABLE MANAGEMENT

▶Ø60 multi-connection socket Black (NE) and white (BA) (on request)

1 power socket + 1USB A + 1USB C



Folded 1-mm thick sheet steel cable riser.

▶ 0.8-mm thick metal tray

ABS side covers in:

- White (BA) with white (BA) structure
- In black (NE) for other structure colours.




ROOF

- Exterior: 1-mm thick folded sheet steel.
- ▶Interior: fabric.



Light fitting for E27 bulbs with switch







DESCRIPTION

STRUCTURE

Welded structure made of 30 mm \times 30 mm \times 2 mm steel profiles, as per UNE-EN 10305. The upper section is joined to the structure with a gable roof made with the same 30 mm \times 30 mm \times 2 mm profiles.

The side panels consist of 12-mm thick melamine and the front panel is 25-mm thick melamine.

The structure is designed for the passage of cabling inside the profiles and has built-in levellers which can be adjusted by 15 mm.

SEATS

The seats consist of a welded steel structure made of 30 mm \times 30 mm \times 2 mm steel profiling and the legs have built-in levellers which can be adjusted by 15 mm.

The seat cushion consists of a 19-mm thick melamine base with 40 kg/m3 foam on top. This joined to the lower structure of the seat with screws and to the side wall with a piece of 1.5mm thick folded sheet steel.

The back rest consists of a 5mm thick MDF support, 30 kg/m3 density foam. Galvanised sheet metal Z brackets are screwed onto it to hang it from the side wall and a 1-mm thick folded sheet steel Z bracket is screwed to the side wall to fix it in place.plegada de acero de 1mm de espesor que se atornilla a la pared lateral.

TABLE

The table is made of a 25-mm thick melamine top surface. The frame consists of two 50 mm \times 30 mm \times 1.5 mm steel profiles and the leg is a steel tube with a diameter of 70 mm.

TECHNICAL SHEET

